

BIG BATT™

DESCRIPTION

Un-faced BIG BATT™ fiberglass insulation for use as thermal and acoustical insulation in attics, walls and floors.

Un-faced BIG BATT™ batts are light density and may be used with a separate vapor barrier.

All BIG BATT™ batts are compression packaged for easy handling and are available in R-values ranging from R-11 to R-38.

Hi-performance and Cathedral ceiling BIG BATT™ batts are available in R-15, R-21, R-30 and R-38 values.

SPECIFICATIONS

ASTM STANDARD C 665 Type I

Thermal Performance (ASTM C 518)

Burning Classification (ASTM E 84)

Flame Spread < 25

Smoke Developed < 50

Water Vapor Sorption (ASTM C 1104)

5% or less by weight

Non-Corrosive (ASTM C 665, 13.8: pass)

Non-combustible (ASTM E 136: pass)

Fungi Resistant (ASTM C 1338: pass)

Critical Radiant Flux >0.12 (ASTM E 970)

Odor Emission (ASTM C 1304: pass)



AVAILABILITY

R-VALUE THICKNESS SIZES

Contact FiberTEK for the availability of non-standard sizes.

R-VALUE	THICKNESS	SIZES
R-11	3.50"	15"X 93", 15"x 105", 16"X 96", 19"X 48", 19"X 93", 23"x 93", 24"x 48", 24"x 96"
R-13	3.50"	15"X 93", 15"x 105", 16"X 96", 19"X 48", 19"X 93", 23"x 93", 24"x 48", 24"x 96"
R-15	3.50"	15"X 93", 15"x 105", 16"X 96", 23"x 93", 24"x 48", 24"x 96"
R-19	6.25"	15"X 48", 15"X 93", 15"x 105", 16"X 96", 19"X 48", 19"X 93", 23"x 93", 24"x 48", 24"x 96"
R-21	5.50"	15"X 93", 15"x 105", 16"X 96", 23"x 93", 24"x 48", 24"x 96"
R-22	6.50"	15"X 93", 15"x 105", 16"X 96", 19"X 48", 19"X 93", 23"x 93", 24"x 48", 24"x 96"
R-25	8.00"	15"X 93", 15"x 105", 16"X 96", 19"X 48", 19"X 93", 23"x 93", 24"x 48", 24"x 96"
R-30	9.50"	16"X 48", 19"X 48", 24"x 48"
R-30C	8.25"	16"X 48", 24"x 48" (Cathedral ceiling batts)
R-38	12.00"	16"X 48", 24"x 48"
R-38C	10.25"	16"X 48", 24"x 48" (Cathedral ceiling batts)