

QWIKBATT™

...as qwik as that!

DESCRIPTION

Kraft QWIKBATT™ fiberglass insulation is intended for use in either residential or commercial construction as thermal and acoustical insulation with an adhered vapor barrier for attics, walls and floors. The kraft facing has no flanges and the batts are cut extra wide for cost effective and quick installation with an easy friction fit.

Standard kraft paper is flammable and should not be used near heat sources such as lights and chimney flues.

Kraft QWIKBATT™ batts are light density and easily cut to fit around wood or metal trusses and joists. Installing this product should save time and improve productivity.

SPECIFICATIONS

ASTM C 764, Type I, Category 1

Density (ASTM C 519)

Kraft: unrated for Flame or Smoke

Water Vapor Sorption (ASTM C 1104)

5% or less by weight

Non-Corrosive (ASTM C 665, 13.8: pass)

Non-combustible (ASTM E 136: pass)

Fungi Resistant (ASTM C 1338: pass)

Critical Radiant Flux >0.12 (ASTM E 970)

Odor Emmision (ASTM C 1304: pass)



No Flange

AVAILABILITY

R-VALUE	THICKNESS	SIZES	
Contact FiberTEK for the availability of non-standard sizes.			
R-13	3.50"	15.25"X 93"	15.25"x 105"
R-15	3.50"	15.25"X 93"	15.25"x 105"
R-19	6.25"	15.25"X 93"	15.25"x 105"
R-21	5.50"	15.25"X 93"	15.25"x 105"

2222 W. Bella Vista Street, Lakeland, Florida 33810 USA
 Phone (863) 682 4448 Fax (863) 603 7688
info@fibertekinsulation.com
www.fibertekinsulation.com



performance fiberglass insulation products